

PRODUCT DATA SHEET

Sika® Drain-500 Mesh Plaster TW

Dimpled protection sheet back-bonded with grid for plastering support

DESCRIPTION

Sika® Drain-500 Mesh Plaster TW is a protection sheet produced from high density polyethylene (HDPE) with 8mm deep dimples. Back side of Sika® Drain-500 Mesh Plaster TW is bonded with grid for plastering support.

USES

As a protection board and damp proofing for different waterproofing systems.

CHARACTERISTICS / ADVANTAGES

- Resistant to impact and mechanical damage
- Resistant to root penetration
- Resistant to all natural aggressive mediums in ground water and soil
- Suitable for contact with soft water (aggressive to concrete)
- Can be installed on damp and wet substrates
- Sika® Drain-500 Mesh Plaster TW can be directly post-plastered by cementitious rendering mortar to save time and labor of metal diamond mesh installation, also without corrosion consideration.

PRODUCT INFORMATION

Packaging	Roll size:	2.00 x 10.00 m
Shelf Life	5 years from date of production if stored properly in undamaged, unopened, original sealed packaging	
Storage Conditions	Rolls must be stored in their original packaging and in cool and dry conditions. They must be protected from direct sunlight, rain, snow and ice, etc	
Appearance / Colour	White HDPE sheet with dimples and grid, total thickness 8 mm.	
Thickness	8.0 (±0.8) mm	(EN ISO 9863-1)
Unit weight	600 (±30) g/m ²	(EN 9864)

TECHNICAL INFORMATION

Compression Resistance	200 (±40) kPa
Tensile Strength	5.5/5.5 (±1) kN/m (MD/CMD) (EN 10319)
Elongation at maximum tensile force	50/50 (±25%) (MD/CMD) (EN 10319)

APPLICATION INFORMATION

Ambient Air Temperature	+ 5 °C min./+ 45 °C max.
--------------------------------	--------------------------

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LIMITATIONS

- Sika® Drain-500 Mesh Plaster TW is not resistant against permanent exposure to weathering and UV-light.
- In combination with PVC membranes, a separation (geotextile) must be used.
- The product is not suitable for mined tunnels because of specific fire resistance regulations.

ECOLOGY

REGULATION (EC) NO 1907/2006 - REACH

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in this product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0.1 % (w/w)

APPLICATION INSTRUCTIONS

SUBSTRATE QUALITY

Clean, sound and dry, homogeneous, free from oils and grease, dust and loose or friable particles.

APPLICATION METHOD / TOOLS

Installation method:

Loose laid and mechanically fastened in accordance with the relevant Sika® application manual and installation instructions.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the declared data for this product may vary from country to country. Please consult the local Product Data Sheet for the exact product data.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika Taiwan Ltd.

15F.-1, No. 83, Sec. 1, Nankan Rd.
Luzhu District
Taoyuan City 338207, Taiwan (R.O.C.)
TEL: 03 352 8622 . FAX: 03 352 0470
Info: sika@tw.sika.com
web: twn.sika.com



Product Data Sheet
Sika® Drain-500 Mesh Plaster TW
March 2022, Version 01.01
02072080110000016

SikaDrain-500MeshPlasterTW-en-TW-(03-2022)-1-1.pdf